



AIR COMPRESSORS INDUSTRIAL RANGE 2 STAGE MACHINE

RATING: 1150 cfm at 500 psi
1350 cfm at 350 psi
543 lps at 34.5 bar
637 lps at 24 bar

The Energy Power Systems Australia range of portable oil flooded rotary screw air compressors are fitted with the latest designed CAT engines Tier 3 for fuel efficiency and reliability. Our fleet of compressors run Sullair rotary screw air ends to provide energy efficiency and reliability. All of our compressors are fitted with user friendly control panels allowing the machine to be operated from the one location.

Our 2 stage high pressure compressors have been designed and built robust for outdoor applications within the drilling, pipeline, and mining segments to provide durability and maintain the production of your operation. The units are open on a skid base and are fully banded to provide protection against ground contamination.

The units are completely assembled with all interconnecting piping and Male BSPP fitting, ready for installation.

POWERED BY EXCELLENCE.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Capacity	1150 / 1,350 cfm 543 / 637 lps
Pressure Range	250 – 500 / 250 – 350 psi 17.2 – 34.5 / 17.2 – 24 bar
Maximum Ambient Temperature	50°C
Open Skid Dimensions	
Length	5,250 mm
Width	2,200 mm
Height	2,600 mm
Weight	7,050 kg (Wet)

FEATURES

- CAT Engine - C18
- Emergency Stop Button
- Sullair Rotary Screw Air End
- Battery Isolator

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney