



**POWERED BY  
EXCELLENCE.**

## AIR COMPRESSORS INDUSTRIAL RANGE

**RATING: 425 cfm at 100 psi  
201 lps at 7 bar**

The Energy Power Systems Australia range of portable oil flooded rotary screw air compressors are fitted with the latest designed CAT engines Tier 2 for fuel efficiency and reliability. Our fleet of compressors run Sullair rotary screw air ends to provide energy efficiency and reliability, the 425 cfm units are fitted with after coolers fitted to provide dry air. All of our compressors are fitted with user friendly control panels allowing the machine to be operated from the one location.

Our compressors have been designed and built robust for outdoor applications within the construction, industrial, pipeline and mining segments to provide durability and maintain the production of your operation. The units are fully enclosed, sound attenuated and are fully bunded to provide protection against ground contamination.

The units are completely assembled with all interconnecting piping and optilock fittings, ready for installation.

### KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Capacity	425 cfm / 201 lps
Pressure Range	80 – 125 psi / 5.5 - 8.6 bar
Maximum Ambient Temperature	50°C
Maximum Towing Speed	89 Km/h
Sound Level	Less than 76 dBA @ 7 meters
Fuel Consumption / capacity	24.8 l/h @ 100% load – 211 litre tank capacity
2 Wheel Road Registered Trailer Dimensions	
Length of Canopy	2,520 mm
Length with Draw Bar	4,120 mm
Width	1,960 mm
Height	1,900 mm
Weight	1,928 kg (Wet)

### FEATURES

- CAT Engine - 3,054C
- Emergency Stop Button
- Sullair Rotary Screw Air End
- Battery Isolator
- After Cooled Air
- Park Brake

**One Network. One Call 1800 800 441 | 24/7 Support**

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney