



AIR COMPRESSORS INDUSTRIAL RANGE

**RATING: 900 cfm at 150 psi
424 Ltr/sec at 10 bar**

The Energy Power Systems Australia range of portable oil flooded rotary screw air compressors are fitted with the latest designed CAT engines Tier 3 for fuel efficiency and reliability. Our fleet of compressors run Sullair rotary screw air ends to provide energy efficiency and reliability, the 900 cfm units are fitted with after coolers fitted to provide dry air. All of our compressors are fitted with user friendly control panels allowing the machine to be operated from the one location.

Our compressors have been designed and built robust for outdoor applications within the industrial, pipeline, mining and construction segments to provide durability and maintain the production of your operation. The units are fully enclosed, sound attenuated and are fully bunded to provide protection against ground contamination.

The units are completely assembled with all interconnecting piping and optilock fittings, ready for installation.

**POWERED BY
EXCELLENCE.**

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Capacity	900 cfm / 424 Ltr/sec
Pressure Range	80 – 150 psi / 5.5 – 10 bar
Maximum Ambient Temperature	50°C
Maximum Towing Speed	10 Km/h
Sound Level	Less than 76 dBA @ 7 meters
Fuel Consumption / Tank Capacity	48.1 Ltr/h @ 100% load / 455 Ltr
Wagon Wheel - 4 Wheel Steerable Dimensions	
Length of Canopy	3,330 mm
Length with Draw Bar	5,180 mm
Width	2,265 mm
Height	2,450 mm
Weight	5,050 kg (Wet)

FEATURES

- CAT Engine - C9
- Emergency Stop Button
- Sullair Rotary Screw Air End
- Battery Isolator
- After Cooled Air
- Park Brake

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney