



**POWERED BY
EXCELLENCE.**

AIR HOSE – 50mm

RATING: 575 psi / 40 bar rating

The Energy Power Systems Australia range of industrial compressed air hoses are manufactured by Alfagomma and are fitted with internal stainless steel wire lanyard and an external galvanized wire stocking. The air hoses are designed for long service life and maximum safety.

Our air hoses have been designed and built robust for outdoor applications within the construction, industrial, pipeline and mining segments to provide durability and maintain the production of your operation.

The hoses are completely assembled with 50mm BSP female fittings, ready for installation.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION,
FOR MORE DETAILS PLEASE CONTACT YOUR LOCAL CAT RENTAL POWER LOCATION

Manufacturer	Alfagomma
Diameter	50mm I.D.
Rated Pressure	575psi / 40 bar
Maximum Pressure	1200psi / 80 bar
Lengths	10mt / 20mt
Standard Fitting	50mm BSP – Female
Colour	Blue

FEATURES

Tube	Black Chlorobutyl – Oil, Mist, High temperature Resistant
Reinforcement	High Tensile Steel Wire Braids
Cover	Blue EPDM – Abrasion and Ozone Resistant
Temperature	-40°C to +150°C with peaks of 232°C
Restraints	Internal – 6mm 7x19 316 stainless steel wire lanyard (minimum braking load 19.5kN) External – galvanized wire stocking with 500mm body length and 90mm anchor eyelet (maximum braking load 71.5kN)

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | www.catrentalpower.com.au

