



**POWERED BY  
EXCELLENCE.**

## AIR MANIFOLDS INDUSTRIAL RANGE

The Energy Power Systems Australia range of industrial air manifolds are fitted with two (2) Type S 2" inlets and six (6) Type A 1" outlets.

Our air manifolds have been designed and built robust for outdoor applications within the construction, industrial, pipeline and mining segments to provide durability and maintain the production of your operation. The units are mounted on forklift pockets for ease of transport.

### KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

|                             |                           |
|-----------------------------|---------------------------|
| Capacity Maximum            | 3,200 cfm / 1,510 Ltr/sec |
| Pressure Maximum            | 150 psi / 10.3 bar        |
| Maximum Ambient Temperature | 50°C                      |
| On Fork Pockets Dimensions  |                           |
| Length                      | 1,325 mm                  |
| Width                       | 470 mm                    |
| Height                      | 430 mm                    |
| Weight                      | 68 kg                     |

### FEATURES

Isolating Gate Valves  
6 x Type A 1" Outlet Fittings  
2 x Type S 2" Inlet Fittings

**One Network. One Call 1800 800 441 | 24/7 Support**

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | [www.catrentalpower.com.au](http://www.catrentalpower.com.au)

