



**POWERED BY
EXCELLENCE.**

BUFFER / SURGE TANKS

RATING: 3000 LTR

The Energy Power Systems Australia range of Buffer Tanks are designed for use with chilled water systems and can be utilised with water, water-glycol and non-aggressive liquids.

All outlets are assembled with all butterfly valves and camlock pipe connections, ready for installation.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Fluid Capacity	3,000 Ltr
Transport Frame Dimensions	
Length	2,400 mm
Width	1,450 mm
Height	1,700 mm
Weight	275 kg (Nominal)

FEATURES

Camlock or Flange Connections
Butterfly Valves Flow Adjustment
Breather Cap

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | www.catrentalpower.com.au

