



**POWERED BY
EXCELLENCE.**

FLUID CHILLERS RATING: 200 kW (NOMINAL)

The Energy Power Systems Australia range of Air Cooled Hermetic Scroll Fluid Chillers are designed for water or water-glycol cooling. All units are designed to be located outside and above ground. The units are completely assembled with all interconnecting refrigerant piping and wiring, ready for installation.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

STACKABLE FRAME

AIR COOLED

HERMETIC SCROLL

Cooling Capacity	224 kW at 6°C Leaving Water Temperature
Absorbed Power	73.8 kW
Temperature Range	-9°C to + 12.8°C
Maximum Ambient Temperature	51.7°C
Transport Frame Dimensions	
Length	3,400 mm (with lifting lugs 3660 mm)
Width	2,470 mm (with lifting lugs 2730 mm)
Height	3,060 mm
Weight	3,800 kg (Nominal)

FEATURES

- 110 Volt Control Circuit
- Emergency Stop Button
- Internal Distribution Board
- Lockable Main Isolator
- Earth Leakage Protection
- 240 Volt Shore Power Connection for Crankcase Heaters to Minimise Chiller Start Up Time
- Condenser Coil Protection
- Flange or Camlock Water Connections

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | www.catrentalpower.com.au

