



**POWERED BY
EXCELLENCE.**

FLUID CHILLERS AIR COOLED RECIPROCATING

RATING: 800 / 1000 kW (NOMINAL)

The Energy Power Systems Australia range of Air Cooled Reciprocating Fluid Chillers are designed for water or water-glycol cooling. All units are designed to be located outside and above ground. The units are completely assembled with all interconnecting refrigerant piping and wiring, ready for installation.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Cooling Capacity	840 kW (50Hz) at 7.2°C Leaving Water Temperature 1,060 kW (60Hz) at 6.7°C Leaving Water Temperature
Absorbed Power	- kW
Temperature Range	-12°C to + 15°C
Maximum Ambient Temperature	54°C
Dimensions 30' ISO Transport Frame	
Length	9,100 mm
Width	2,440 mm
Height	2,940 mm
Weight	16,600 kg (Nominal)

FEATURES

- 110 Volt Control Circuit
- Emergency Stop Button
- Internal Distribution Board
- Lockable Main Isolator
- Earth Leakage Protection
- 240 Volt Shore Power Connection for Crankcase Heaters to Minimise Chiller Start Up Time
- Fire Detectors
- Condenser Coil Protection
- Flange or Camlock Water Connections

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | www.catrentalpower.com.au

