



**POWERED BY
EXCELLENCE.**

FLUID PUMPS CENTRIFUGAL RANGE

RATING: 30 Ltr/sec (NOMINAL)

The Energy Power Systems Australia range of Fluid Pumps are designed for use in the refrigeration industry for the circulation of chilled water or water-glycol.

All units are designed to match the requirements of our range of rental fluid chillers and air handlers. The units are completely assembled with camlock connections for piping and wiring, ready for installation and have been placed in a robust transport skid.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Design Flow	21 Ltr/sec
Design Pressure Head	30 Mtr
Absorbed Power At Duty Point	9.48 kW
Installed Motor Rating	15 kW
Transport Skid Dimensions	
Length	1,700 mm
Width	620 mm
Height	1,200 mm
Weight	520 kg (Nominal)

FEATURES

- Camlock Connections
- Butterfly Valve Flow Adjustment
- Motor Soft Start
- 110 Volt Control Circuit (option)
- E/Stop (option)
- 32 amp Marechal Socket Connection
- Pressure Gauge

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney