



**POWERED BY
EXCELLENCE.**

FLUID PUMPS CENTRIFUGAL RANGE

RATING: 80 Ltr/sec (NOMINAL)

The Energy Power Systems Australia range of Fluid Pumps are designed for use in the refrigeration industry for the circulation of chilled water or water-glycol.

All units are designed to match the requirements of our range of rental fluid chillers and air handlers. The units are completely assembled with camlock connections for piping and wiring, ready for installation and have been placed in a robust transport skid.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

| | |
|------------------------------|------------------|
| Design Flow | 77.5 Ltr/sec |
| Design Pressure Head | 30 Mtr |
| Absorbed Power At Duty Point | 29.3 kW |
| Installed Motor Rating | 37 kW |
| Transport Skid Dimensions | |
| Length | 1,700 mm |
| Width | 630 mm |
| Height | 1,400 mm |
| Weight | 560 kg (Nominal) |

FEATURES

- Camlock Connections
- Butterfly Valve Flow Adjustment
- Motor Soft Start
- 110 Volt Control Circuit (option)
- E/Stop (option)
- 32 amp Marechal Socket Connection
- Pressure Gauge

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | www.catrentalpower.com.au

