



**POWERED BY
EXCELLENCE.**

HEAT EXCHANGERS STAINLESS STEEL PLATE / GASKETED

RATING: 700 kW (NOMINAL)

The Energy Power Systems Australia range of Heat Exchangers are designed for separation of aggressive liquids in a chilled water or water-glycol circuit. All units are designed to be located outside and above ground.

The units are completely assembled with stainless steel camlock fluid connections, ready for installation.

KEY DATA

THIS IS SUMMARY DATA INFORMATION ONLY AND IS NOT FULL SPECIFICATION, SOME EQUIPMENT MAY VARY.

Design Heat Exchange	711 kW
Type	Plate
Design Flow	30 Kg/sec
Transport Skid Dimensions	
Length	1,200 mm
Width	800 mm
Height	1,350 mm
Weight	530 kg (Nominal)

FEATURES

- Camlock or Flange Connections
- Stainless Steel Fittings
- Stainless Steel Plates - Cleanable
- Other Medium Cooling (Option) – P.O.A.

One Network. One Call 1800 800 441 | 24/7 Support

Melbourne | Adelaide | Perth | Darwin | Townsville | Rockhampton | Brisbane | Sydney

ABN 80 055 274 514

CAT®, CATERPILLAR®, their respective logos, "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2008 Caterpillar All Rights Reserved

Energy Power Systems Australia Pty Ltd | www.catrentalpower.com.au

